

# AXPERT MAX II

OFF - GRID INVERTER



- Indicación de estado con luces RGB
- Wi-Fi incorporado para monitoreo móvil (la aplicación Android/iOS disponible)
- Admite la función USB On the Go
- Puerto de comunicación reservado para BMS (RS485, CAN-BUS o RS232)
- Diseño de ventilador reemplazable para facilitar el mantenimiento
- Diseño independiente de la batería

# AXPERT MAX II

OFF - GRID INVERTER



MODEL	AXPERT MAX II
Rated Power	6500VA/6500W
Parallel Capability	YES, 6 units
<b>INPUT</b>	
Voltage	120 VAC
Selectable Voltage Range	90-140 VAC (For Computers) ; 80-140 VAC (For Home Appliances)
Frequency Range	50 Hz/60 Hz (Auto sensing)
<b>OUTPUT</b>	
AC Voltage Regulation (Batt. Mode)	120VAC ± 5%
Surge Power	13000VA
Efficiency (Peak)	91%
Transfer Time	15 ms (For Personal Computers), 20 ms (For Home Appliances)
Waveform	Pure sine wave
No Load Power Consumption	< 75W
DC Voltage	12 VDC ± 5%, 100W
<b>BATTERY</b>	
Battery Voltage	48 VDC
Floating Charge Voltage	54 VDC
Overcharge Protection	66 VDC
<b>SOLAR CHARGER &amp; AC CHARGER</b>	
Solar Charger Type	MPPT
Maximum PV Array Power	8000W (4000W x 2)
MPPT Range @ Operating Voltage	90 ~ 230 VDC
Maximum PV Array Open Circuit Voltage	250 VDC
Maximum Solar Charge Current	120A
Maximum AC Charge Current	120A
Maximum Charge Current	120A
<b>PHYSICAL</b>	
Dimension, D x W x H (mm)	158.4 x 503.6 x 530.8
Net Weight (kgs)	20
Communication Interface	USB/RS232/RS485/WiFi/Dry-contact
<b>OPERATING ENVIRONMENT</b>	
Humidity	5% to 95% Relative Humidity(Non-condensing)
Operating Temperature	-10°C to 50°C
Storage Temperature	-15°C to 60°C
<b>STANDARD</b>	
Compliance Safety	UL